

# S

High-Performance

# ABRASION AND HEAT RESISTANT

Aluminum Extrusion Belting

ROLLER COVERS, BELTS, PADS, & SPACER SLEEVES





**SHIPP**  
BELTING

**24-HOUR  
ON-DEMAND  
EXPERT  
SERVICE**

Aluminum Extrusion Belting is designed to withstand extreme temperatures and deliver superior performance in adverse applications. Whatever size you need, our team of experts will work with you to create a solution tailored to your needs. And with some of the fastest lead times and 80 years of custom fabrication services, you can be confident that you're getting the best quality and personal service in the industry.


We are committed to being there when you need us. That's why we offer make & hold stock programs to help you plan ahead and have as little down time as possible.

You can trust Shipp Belting to provide the results you need to keep your business moving in the right direction.



## WE OFFER HEAT RESISTANT:

ROLLER COVERS,  
BELTS, PADS,  
& SPACER SLEEVES



### Common Applications:

- ▶ In-Feed Lines
- ▶ Exit Lines
- ▶ Forming Lines
- ▶ Cooling / Quenching Lines
- ▶ Pick-Up Table
- ▶ Spacer Bar Sleeves
- ▶ Cooling Table
- ▶ Sizing Table
- ▶ Puller and Run-Out Table
- ▶ Sawing Station
- ▶ Deburring
- ▶ Walking Table

### Features Available:

- ▶ Durable Materials
  - ▶ Extreme Temperature Resistant
  - ▶ Abrasion Resistant
  - ▶ Endless, Welded or Pin Splicing
  - ▶ Timing and Synchronization
  - ▶ Special Covers: Non-Marking Kevlar®, PBO, Nomex and Polyester
  - ▶ Heavy Load Capable
  - ▶ Antistatic
- ▶ Non-Slip
  - ▶ No Delaminating
  - ▶ Fabrications such as vacuum draw, cleats, holes, pockets, guides, custom coatings and more



# Heat resistance in ranges from 392°F to 1202°F

### ROLLER COVERS

**Materials:**  
Kevlar, PBO,  
Polyester, Nomex,  
Kevlar/Carbon

**Inside Diameter  
Sizes (mm):**  
20 to 180

**Wall Thickness  
(mm):** 6, 8, 10, 12

**Length:** Per request

**Weight:**  
>410 g/m<sup>2</sup>/mm

### ENDLESS BELTS

**Materials:**  
Kevlar, PBO,  
Polyester, Nomex,  
Kevlar/Carbon

**Width (mm):**  
20 to 2000

**Thickness (mm):**  
6, 8, 10, 12

**Length (mm):**  
per request from  
540 to 13500

**Weight:**  
>410 g/m<sup>2</sup>/mm

### PADS

**Materials:**  
Kevlar, PBO,  
Polyester, Nomex,  
Kevlar/Carbon

**Width (mm):**  
20 to 2000

**Thickness (mm):**  
6, 8, 10, 12, 15

**Length (mm):**  
per request from  
50 to 25000

**Weight:**  
>410 g/m<sup>2</sup>/mm

### SPACER COVERS

**Materials:**  
Nomex

**Thickness (mm):**  
0.8 - 1.5

**Weight:**  
210 - 250 g/m<sup>2</sup>

**We guarantee consistent  
and timely service to all of our  
partners, no matter what.  
When you choose Shipp Belting,  
you choose to minimize costly  
downtime and meet sanitary  
regulations for your modern,  
high-speed equipment.**

**Have a Belt Problem? We can help.**



**SHIPP**  
BELTING

Daily Assistance  
& Emergency Service  
(254) 776-0493

*[shippbelting.com](http://shippbelting.com)*

Shipp Belting Company  
123 S. Industrial Dr,  
Waco, TX 76710